

Kebu® PVC - insulation tape

DATA SHEET

- Excellent electrical insulation
- Good adhesion
- Elastic
- UV-resistant
- Humidity-resistant
- Waterproof



The Kebu® PVC - insulation tape is a universally applicable adhesive tape. It consists of an adhesive layer of synthetic rubber. Suitable application purposes are the insulation, bundling, repairing or marking of wires.

The product fulfills the requirements of the RoHS and Reach guidelines and is certified according to VDE.

Forms of delivery

Available in the following colors: black, red, blue, white, yellow, brown, green and grey.

	Length of roll [m]	Width of roll [mm]	Rolls per box [-]	Content of box [m²]
PVC - insulation tape	10	15	40	6,00
	10	19	32	6,08
	10	50	22	11,00
	10	100	12	12,00

Properties

Property	Unit	Typical values
Thickness	mm	≈ 0.13
Dielectric strength	kV	min. 5.2
Temperature resistance	°C	- 10 up to 85
Tensile strength	N/cm	min. 13
Adhesion on steel surfaces	N/cm	min 1.8
Elongation at break	%	min. 100

Storage

The tapes must be stored in the original package at a dry location.

The recommended storage temperature is between -5 °C and + 40 °C.

The information given in this publication is based on our knowledge and experience. The hints and instructions for use given therein have been compiled to the best of our knowledge on the basis of our tests and experience. Best results will be obtained if our products are used in a proper and expert way. Any protected rights and existing laws and regulations must be complied with the recipient. In all other respects our general terms and conditions shall apply.

-- Rev.: 00_18.03.2019 --