

# Kebu Plast Mastic

## PRODUCT DATA SHEET

- cold applied mastic
- based on petrolatum
- solvent-free



**Kebu Plast Mastic** is a filling compound based on petrolatum to fill in void risk areas, for example for wrapping valves and flanges with petrolatum tapes. It consists of industrial petrolatum, fillers and fibres.

The area to be coated must be dry and free of dust and grease. If necessary, dry the surface using a propane torch or use **Kebu Petro Primer**. There is no need to preheat the area. A surface cleanliness of St 2 according to 8501-1 is sufficient for this application. Take **Kebu Plast Mastic** from the packaging, kneading it by hand or with a spatula. It is suitable for the application in void risk areas like gorges, around screws, nuts as well as for gaps between flanges. Subsequent the **Kebu Plast Mastic** needs to be coated by a suitable petrolatum tape, like **Kebu Petro-Tape A303** with the required number of layers.

### FORMS OF DELIVERY

Store cool and dry.

	Container capacity [l]	Weight [kg]
Kebu Plast Mastic	Plastic bag	0,5
	Carton	7,5
		12,5

### PROPERTIES

Property	Unit	Typical values
Colour	-	brown
Consistency	-	deformable
Congealing point	°C	> 60
Operating temperature	°C	≤ 30
Processing temperature	°C	5 - 30
Saponification number	mg KOH/g	max. 2

The information given in this publication is based on our knowledge and experience. The hints and instructions for use given therein have been compiled to the best of our knowledge on the basis of our tests and experience. Best results will be obtained if our products are used in a proper and expert way. Any protected rights and existing laws and regulations must be complied with the recipient. In all other respects our general terms and conditions shall apply.  
 -- Rev.: 01\_21.10.2020 --